

## ***Innovative | Interactive | Intelligent***

**The 2700 CE is the most advanced, next generation ATM for the retail market.**

### **Design**

The modern, yet simple design of the 2700 CE looks like no other ATM before its time. The elegant lines of the 2700 CE allows it to fit in, and even enhance, any setting. The optional LED topper or LCD topper are powerful advertising tools and seamless extensions of the ATM.

### **Dynamic User Interface**



The 2700 CE's highly advanced user interface and graphics compliments the design. Enhanced features include streaming news and weather updates, background changes, advertising capability, and vibrating touch screen.

### **More Power and Security**

The ARM v7 Cortex A8 834MHz CPU, has expert data processing capabilities to power multitasking, networking, and enhanced graphics & audio.

Enhanced security features ensure the highest level of security of any ATM:

#### **Security Options**

- Anti-Skimming (Skimmer's device detector)
- Security Pack (Thermal Sensor, Vibration Sensor, Local Siren)
- Auto remote report (with RMS system)
- Enhanced safe door and locking mechanism



## **Innovative | Interactive | Intelligent**

**The 2700 CE is the most advanced, cost effective ATM on the market.**



**System Control**

- ARM v7 Cortex A8
- Microsoft® Windows CE 6.0

**Customer Display**

- 10.2" TFT LCD

**Communication**

- TCP/IP (SSL configurable)

**Optional**

- Dial-up

**Input Type**

- 4x2 touch function keys

**Optional**

- 10.2" TFT touch screen with vibrating feedback

**Languages**

- English
- Spanish
- French

**Card Handling**

- Dip-type card reader

**Optional**

- IC card reader EMV Level 1, 2 compliant

**Cash Dispensing**

- 1,000 or 2,000-note removable cassette  
Up to Three cassettes

**Printers**

- 80 mm graphical thermal receipt printer

**Security**

- UL Business Hour safe
- Mechanical combination lock
- Security Options
  - UL Level 1 safe
  - Electronic safe lock
  - KABA Mas Cencon safe lock
  - Alarm Box Option
  - Proximity Sensor Option
  - Camera Option

**Power Supply**

- AC 110–230V, 50–60 Hz

**Operating Environment**

- Temperature: -32°F–104°F
- Humidity: 25%–85%

**Dimension and Weight**

- Height: 52.3" (1,328 mm)
- With Topper: 66.3" (1,685 mm)
- Width: 15.7" (400 mm)
- Depth: 18.4" (468 mm)
- Weight: 265 lbs (120 kg)



**Illuminated Topper**

Optional Double sided LED Back-Light  
Optional 15" LCD

LED Back-Lit ATM Sign

**Function Keys**

(4x4 touch function keys)

**Receipt Printer**

Graphical thermal printer  
Prevents paper jam  
80 mm thermal receipt paper  
Automatic paper loading and cutting

**Customer Display**

10.2" wide TFT Color LCD  
Infrared Touch Screen Option

**Card Reader**

Dip hybrid card reader  
EMV level 1, 2 support (EMV 4.0)

**EPP**

PCI compliant EPP  
Triple DES compliant  
RKT Option

**Cash Dispensing Unit**

Up to 3 cassettes containing 1,000 or 2,000 bank notes  
Dispensing speed 6 notes per second  
Double detection sensor  
Reject cassette